

LEVEL-QUICK

2D

AN INTERIOR, UNDERLAYMENT MATERIAL USED TO PATCH AND LEVEL A VARIETY OF SURFACES PRIOR TO APPLYING FLOOR COVERINGS

LEVEL-QUICK is a fast-setting, interior, underlayment material used to patch and level wood, concrete, plaster and tile floors. Use Level-Quick to fill cracks, nail holes, knots and wear spots before applying floor coverings such as linoleum, vinyl, rubber, asphalt tile, core composition, ceramic tile or carpeting.

USES and ADVANTAGES

- Bonds to wood, concrete, plaster, masonry and tile.
- Fills cracks, nail holes and joint lines in wood sub floors.
- Use to smooth imperfections in wood floors such as low spots and knots
- Can be feather-edged.
- Provides a smooth surface for resilient flooring or carpeting.
- Use to equalize floor levels.
- Easily applied with trowel or broad knife.
- Easy to use, just mix with water.
- Non-shrinking.
- Sets in only 15 minutes.
- Can be walked on in 1 hour.

SURFACE PREPARATION

All surfaces must be sound and clean. Remove all dirt, dust, spalling or loose concrete, oil, grease, wax, mildew, efflorescence, curing compounds, form release agents, paint or any other foreign material which might effect the bond. Concrete surfaces should be fully cured. Dampen concrete and masonry surfaces with water before applying Level-Quick, being careful not leave any standing water. If the surface is very smooth and non-absorbent, such as ceramic tile and terrazzo, prime the area with Umaco Bond All Exterior.

Apply Level-Quick while Bond All Exterior is still tacky and damp to the touch.

Always perform a spot test (of sufficient size) prior to application in order to ensure compatibility between Level-Quick and the substrate as well as to confirm that the appearance and performance are acceptable.

MIXING

In a clean container, add enough clean water to the Level-Quick then mix to form a thick but workable consistency. Add approximately one gallon of water for every 25 pounds of Level-Quick. Mix thoroughly but **do not over mix and do not use an excessive amount of water.**

APPLICATION

Spread Level-Quick with broad putty knife or trowel to desired thickness. Immediately finish surface with a steel trowel. Clean tools with water immediately after use. Level-Quick achieves maximum hardness after 3 hours. Once fully hardened, it can be sanded to a smoother finish.

COVERAGE

One 50 pound bag will cover approximately 70 square feet at 1/8" thickness.

TECHNICAL DATA

Set Time.....15 minutes
Compressive Strength.....2,300 psi

PRECAUTIONS

- Do not use below grade.
- Do not use in wet areas or where moisture may be present.

WARNING!

Contains Calcium Sulfate. If ingested, may result in obstruction. If ingested, induce vomiting using large quantities of milk and call physician immediately. Avoid inhalation. Use only with adequate ventilation. If affected by inhalation, get fresh air immediately. To avoid possible burns or irritation, avoid eye and skin contact by wearing safety glasses and rubber gloves. In case of eye contact, flush thoroughly with water and get prompt medical attention. In case of skin contact, wash thoroughly with soap and water. If irritation persists, consult a physician. Read Material Safety Data Sheet (MSDS) before using this product which may be obtained from your dealer or by calling 978-453-8881.

24 Hour Emergency Medical/Spill Information (Chemtrec): 800-424-9300

KEEP OUT OF THE REACH OF CHILDREN!

For technical assistance call
978-453-8881

www.umaco.com

LIMITED WARRANTY

The manufacturer guarantees its products to be free of defects and the extent of its liability is limited to the purchase price of the materials only, if proved to be defective. Improper mixing, incorrect application or other factors beyond the control of the manufacturer or its dealers may produce unsatisfactory results and cannot be held to be the manufacturers or it's dealers responsibility. There are no other guarantees either expressed or implied.

03-01-05



60 REAR NEWHALL STREET

PHONE: 978-453-8881

LOWELL, MA. 01852

FAX: 978-453-2416