

BLOCK-LOCK ADHESIVE 4E

PROVIDES A STRONG, DURABLE BOND WHEN INSTALLING CAPS TO LANDSCAPE BLOCK WALLS OR PAVERS TO CONCRETE SUBSTRATES

BLOCK-LOCK ADHESIVE

is designed to adhere final course caps to landscape block walls and may also be used to bond (horizontally) a variety of other materials such as pavers, limestone, granite, concrete and untreated wood. Block-Lock Adhesive provides exceptional adhesion and resistance to tear, shear, stress and weathering. May be applied to damp surfaces in a wide range of temperatures.

USES and ADVANTAGES

- Provides a strong durable bond when installing caps to landscape block walls.
- May be applied to damp, non-porous surfaces in a wide range of temperatures.
- Bonds to a variety of materials including pavers, limestone, granite, concrete and untreated wood.
- Easily applied with a standard caulk gun.

SURFACE PREPARATION

Surfaces to which adhesive is being applied must be clean and structurally sound. All foreign materials such as dirt, dust, oils, grease, soot, loose paint, etc. should be removed before applying adhesive. Do not use xylene or MEK to clean surfaces unless the surface can be allowed to dry before application of the adhesive.

APPLICATION

Landscape Block

When installing caps onto landscape block walls, use a 1/4" bead approximately 2" in from the front and 2" in from the back. Then set cap by

gently pushing down with a twisting motion.

Concrete Pavers

When installing pavers, apply an "s" bead approximately 1/4" onto the back of the paver being applied directly to the concrete. Then set paver by gently pushing down with a twisting motion.

Keep foot traffic off landscape block wall caps or concrete pavers for 24-48 hours after application.

For areas subject to heavy traffic; keep off for 4-5 days.

Service Temperature

- -40 degrees F to 180 degrees F.
- -40 degrees C to 82 degrees C

COVERAGE

One 10.6 oz. cartridge will yield approximately 32 linear feet at a 1/4" bead.

CLEANING

Remove material from gun and tools before it cures by scraping and/or the use of solvents such as xylene or MEK. Cured materials may be removed by cutting with sharp tools or sandpapering. Observe manufacturer's precautions when using toxic or flammable solvents.

PRECAUTIONS

- Do not use in areas where food is processed or stored unless material is cured completely at least 14 days at room temperature.
- Block-Lock Adhesive will cause asphalt, Styrofoam and some plastic products to dissolve.
- When temperature is below 10

degrees F, application will be easier if the adhesive is warmed.

- Do not use for applications continuously submerged in water or below grade.

WARNING!

Combustible (during cure). Keep away from sparks and open flame. Contains PM acetate and aromatic hydrocarbons. Harmful or fatal if ingested. If swallowed do not induce vomiting. Call physician. May be harmful if inhaled in an enclosed space. Use only in a well ventilated area. Avoid prolonged skin contact. Read Material Safety Data Sheet (MSDS) before using this product which may be obtained from your retailer or by calling 978-453-8881.

24 Hour Emergency Medical/Spill Information (Chemtrec): 800-424-9300.

USE ONLY WITH ADEQUATE VENTILATION.

KEEP OUT OF THE REACH OF CHILDREN.

For technical assistance call 978-453-8881

www.umaco.com

LIMITED WARRANTY

The manufacturer guarantees its products to be free of defects and the extent of its liability is limited to the purchase price of the materials only, if proved to be defective. Improper mixing, incorrect application or other factors beyond the control of the manufacturer or its dealers may produce unsatisfactory results and cannot be held to be the manufacturers or its dealers responsibility. There are no other guarantees either expressed or implied. 03-01-05



60 REAR NEWHALL STREET

PHONE: 978-453-8881

LOWELL, MA. 01852

FAX: 978-453-2416